



BEST VALUE IMPORT FOR B200 DIRECT REPLACEMENT POWER CHUCKS

HIGH QUALITY • EXCELLENT PERFORMANCE • BEST VALUE

Free Standard Length Draw Nut Machined to Fit your Machine

3-Jaw Power Chucks				
Dia	Model #	Thru-Hole	RPM	List Price
4"	BL04B-3	1.02	8000	\$1,595.00
5"	BL05B-3	1.30	7000	\$1,742.00
6"	BL06B-3	1.77	6000	\$1,765.00
8"	BL08B-3	2.05	4700	\$2,415.00
10"	BL10B-3	2.95	4200	\$2,995.00
12"	BL12B-3	3.58	3200	\$3,465.00
15"	BL15B-3	4.65	2800	\$6,565.00
18"	BL18B-3	4.65	2000	POA
21"	BL21B-3	5.51	1600	POA
24"	BL24B-3	6.61	1300	POA
28"	BL28B-3	8.27	1000	POA

2-Jaw	Power Chucks
Diameter	Model #
6"	BL06B-2
8"	BL08B-2
10"	BL010B-2
12"	BL012B-2

4-Jaw	Power Chucks
Diameter	Model #
6"	BL06B-4
8"	BL08B-4
10"	BL010B-4
12"	BL012B-4

2/3 Jaw	Combination	Power	Chucks
Dia	Model #	Thru-Hole	RPM
8"	BL08B-2/3	2.05	3000
10"	BL10B-2/3	2.95	2500
12"	BL12B-2/3	3.58	2000



Model	Thru-Hole Dia (in)	Stroke (in)	Jaw Stroke (in)	RPM	Cylinder	Weight (lbs)
BL04B	1.02	0.39	0.17	8000	H036	8
BL05B	1.30	0.39	0.17	7000	H036	15
BL06B	1.77	0.47	0.20	6000	H046	28
BL08B	2.05	0.63	0.27	4700	H052	50
BL10B	2.95	0.75	0.31	4200	H075	78
BL12B	3.58	0.90	0.39	3200	H091	136
BL15B	4.65	0.90	0.39	2800	H0118	242
BL18B	4.65	0.90	0.39	2000	H0118	348
BL21B	5.51	0.90	0.39	1600	H0140	502
BL24B	6.61	0.90	0.39	1300	H0140	629
BL28B	8.27	0.90	0.39	1000	H0140	924

DIMENSIONS

Model	A	B	C	D	E	F	G	H	I	J min	J max	K	L min	L max	M	N	O	P	Q	R
BL04B	4	3.3	3.0	A2-3	M32x1.5	1.0	0.5	0.6	1.1	0.2	0.1	0.9	0.04	-0.30	0.7	0.5	0.2	2.4	M10	0.9
BL05B	5	4.3	3.3	A2-4	M40x1.5	1.3	0.6	0.7	1.1	0.3	0.2	1.2	0.04	-0.30	0.8	0.5	0.2	2.4	M10	0.9
BL06B	6.7	5.5	4.1	A2-5	M55x2.0	1.8	0.6	0.8	1.5	0.3	0.2	1.4	0.40	-0.04	0.8	0.6	0.2	3.2	M10	1.3
BL08B	8	6.7	5.3	A2-6	M60x2.0	2.1	0.9	1.0	1.8	0.4	0.2	1.5	0.60	-0.08	0.8	0.7	0.2	3.6	M12	1.4
BL10B	10	8.7	6.7	A2-8	M85-2.0	3.0	1.2	1.2	2.0	0.6	0.5	1.7	0.30	-0.40	1.0	0.7	0.2	3.9	M16	1.6
BL12B	12	8.7	6.7	A2-8	M100x2.0	3.7	1.5	1.2	2.4	0.9	0.7	2.0	0.30	-0.60	1.1	0.7	0.2	4.3	M16	2.0
BL15B	15	12	9.3	A2-8	M130x2.0	4.6	1.4	1.7	2.4	2.0	1.8	2.8	0.40	-0.50	1.1	0.9	0.2	5.1	M20	2.4
BL18B	18	15	9.3	A2-11	M130x2.0	4.6	1.6	2.4	3.1	2.2	2.0	2.8	0.40	-0.50	1.1	0.9	0.2	5.7	M20	2.6
BL21B	21	15	13	A2-15	M155x3.0	5.5	1.6	3.1	3.1	3.6	3.4	3.1	0.40	-0.50	1.3	1.1	0.2	5.9	M22	2.8
BL24B	24	15	13	A2-15	M175x3.0	7.1	1.6	3.1	3.5	4.8	4.6	3.5	0.90	-0.04	1.3	1.1	0.2	6.3	M22	3.0
BL28B	28	20	18	A2-20	M220-3.0	8.3	2.0	3.5	3.9	5.3	5.1	3.9	0.90	-0	1.4	1.1	0.2	6.9	M24	3.1